


ISDN S-INTERFACE TRANSFORMERS

Surface Mount, Dual, 2000 Vrms

MACONICS
MAGNETICS SOLUTION FOR 3C



Electrical Specifications @ 25°C — Operating Temperature 0°C to 70°C

Part Number	Ratio (±2%)		OCL Pri (mH MIN)	L _L Sec (μH MAX)		C _{w/w} (pF MAX)	CD Pri (pF MAX)		DCR Pri (Ω ±25%)		DCR Sec (Ω ±5%)		D I _{bc} (mA MAX)	Package/ Schematic
	A	B		A	B		A	B	A	B	A	B		
MR-76803	1:1	1:2	22	5	15	100	42	80	2.4	2.3	2.4	4.0	1	A1
MR-76804	1:1	1:1	22	5	5	100	42	42	2.4	2.4	2.4	2.4	1	A1
MR-76806	1:2	1:2	22	15	15	100	80	80	2.5	2.5	4.3	4.3	1	A1
MR-76809	1:2.5	1:2.5	22	8-40	8-40	100	110	110	2.5	2.5	5.8	5.8	1	A1
MR-76800	1:2	1:2	22	11	11	100	180	180	2.4	2.4	4.4	4.4	1	A1

Mechanical

Schematic

A1

